

To: CN=Jose Zambrana/OU=DC/O=USEPA/C=US@EPA;CN=Ramona
 Trovato/OU=DC/O=USEPA/C=US@EPA[]; N=Ramona Trovato/OU=DC/O=USEPA/C=US@EPA[]
Cc: CN=Cynthia Sonich-Mullin/OU=CI/O=USEPA/C=US@EPA[]
From: CN=Kelly Smith/OU=ADA/O=USEPA/C=US
Sent: Tue 10/23/2012 10:27:35 PM
Subject: well installation
[EPA_ReportOnPavillion_Dec-8-2011.pdf](#)
[ATT0OZAD.pdf](#)
[ATT8GX3V.pdf](#)
[ATT17ZDJ.pdf](#)
[Chapter 11. MW Conditions with Attached Borehole and Well Detail 2006.pdf](#)
[ATTFHIIQ.pdf](#)

Attached is the reference materials for the well installation.

Document	File	Page	Screen	Casing
EPA QAPP	Pavillion QAPPv0.pDF	12		Determine well screen materials to ensure a minimum internal diameter of 4 inches. Determine casing materials to ensure a minimum internal diameter of 4 inches.
Shaw QAPP	MW_Installation_Workplan_for Drilling.pdf			MWIWP Worksheet #14
	page 1 of 3		4" ID	threaded stainless steel
			4" steel riser	
Shaw Workplan Attachment_1_Monitoring_Well_Installation_Narrative		3-10		5"ID threaded stainless steel
			5" ID flush-threaded steel casing or Schedule 80 PVC	
Draft Report	EPA_ReportOnPavillion_Dec-8-2011	9-10, schematic	Stainless steel	4" stainless steel
Well Standards Attachment_1_Monitoring_Well_Installation_Narrative		6		
Section 67 (a)(i)(III)				
Page 12			Factory screen casing is recommended for the perforated section of the well.	Allows for ASTM A53

Kelly A. Smith
 Applied Research & Technical Support Branch

U.S. Environmental Protection Agency
 Office of Research and Development
 National Risk Management Research Laboratory
 Ground Water and Ecosystem Restoration Division
 919 Kerr Research Drive
 Ada, Oklahoma 74820
 (580) 436-8805 (Office)